



SS500 - DAILY OPERATOR CHECKLIST

PRE-OPERATION CHECKLIST

- Check the battery fluid and charge level
- Fill the Automatic Battery Watering reservoir with DISTILLED WATER, if equipped.
- Fill the Severe Environment™ (SE) detergent reservoir with detergent, if equipped.
- Check the tank cover seals for damage and wear
- Clean the vacuum fan inlet filter
- Check the condition of the scrubbing brushes
(Remove any string, banding, plastic wrap, or other debris wrapped around them)
- Check the squeegees for damage, wear and for deflection adjustment
- Check the vacuum hose for debris or blockage
- Drain and clean the recovery tank
- ec-H2O NanoClean™ Scrubbing: Ensure the solution tank is filled with clear cool water only
- Check the service records to determine maintenance requirements

POST-OPERATIONAL CHECKLIST

- Clean the solution and recovery tanks
 - Clean the vacuum fan inlet filter
 - Check the scrub head and brushes for banding, plastic wrap and twine
 - Check the squeegees for damage or wear
 - Check the vacuum hoses for debris or blockage
 - Check the battery charge levels to determine if the batteries need charging
 - Check the fluid level of all battery cells and place the machine on the charger, if needed.
 - Fill the Automatic Battery Watering reservoir with DISTILLED WATER, if equipped.
- List below any problems that occurred during operation.

OPERATOR _____ **DATE** _____

SUPERVISOR _____ **DATE** _____