

# Heavy Duty Upright Vacuum



## A versatile heavy duty upright vacuum cleaner for everyday use.



### Increase user comfort

The vacuum's spring-assisted design means lighter handle weight and less operator fatigue. The ergonomic handle is designed to fit every operator comfortably.

### Robust performance

This upright vacuum is designed for years of use with its rotationally-molded base and robust foot latch. Three levels of filtration down to .1 micron at 99.99% efficiency help improve indoor air quality.

### Productive product features

With variable height settings, this unit accommodates a variety of floor surfaces. Low profile capabilities allow the vacuum to lay flat to clean under hard to reach areas.

## Key Benefits

- Rotationally-molded base is more durable than commonly used injected molded plastic
- Dual motor design with separate vacuum and brush motors deliver powerful, dirt-lifting suction
- Multi-signal indicator light alerts for product and user safety



# Heavy Duty Upright Vacuum



Features	Specifications*
<b>Product Name</b>	V-HDU-14
<b>Vacuum System</b> Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	125 cfm / 3.54 m <sup>3</sup> /h 1 hp / .75 kW each Through flow, single stage, thermal protected 915 watts / 7.9 A 80 in / 2030 mm
<b>Brush Drive System</b> Brush belt description Brush type Brush size Brush motor HP Brush motor RPM Brush RPM Brush height	Dual, round drive belts Single row, chevron pattern 2.25 / 57 mm in diameter, 12 in / 305 mm length 0.1 hp / .07 kW 6000 3000 Adjustable to 6 positions with manual dial
<b>Filtration</b> Triple filtration system Triple filtration description Vacuum bag capacity Vacuum hose length	Filter bag, vac motor filter, and post filter High efficiency (99.9%) at 0.3 micron Top fill design, 5.2 qt / 5 L 1.5 ft / 0.46 m (4:1 stretch ratio)
<b>Electrical</b> Electrical system Indicator light Power cord length	Printed circuit board protected Multi - Signal light system for improved safety 40 ft / 12 m
<b>Chassis/Body Construction</b> Construction	Rotationally-molded polyethylene
<b>Accessories</b> Standard Optional	On-board crevice tool, swivel wand and flex hose Dusting brush, wall and upholstery tool
<b>Dimensions / Weight / Sound Level</b> Length Width Height Weight Sound level (at operator's ear)	14.5 in / 368 mm 14 in / 356 mm 47 in / 1190 mm 21 lb / 9.53 kg 69.5 dBA
<b>Approvals</b>	CSA, ETL
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice